



QDE-Jr Distribution & Drop Amplifier:

Features:

- ▶ Single-hybrid RF amplifier configured to serve house drop or low-power distribution amplifier application
- ▶ Push-pull technology to 860 MHz
- ▶ Cost-effective, 1-way or 2-way amplifier
- ▶ 2-way versions include passive return path with 2 dB loss or may have optional plug-in transistor return amplifier with 20 dB of gain
- ▶ 5-30 or 5-40 MHz return path
- ▶ Fixed-tuned with full range of pads & EQs
- ▶ Gains: 17, 21, 25 or 32 dB
- ▶ Test points are -30 dB at the input & output of the 25 & 32 dB gain models to monitor signal levels
- ▶ 1-way, sub return models for headends available from 5-50 MHz or 5-200 MHz with gains of 17, 21, 23, & 28 dB
- ▶ One model includes internal 45 MHz lowpass filter for I.F. or lower frequency specialty applications
- ▶ Housing provides efficient thermal capability & stringent RFI shielding
- ▶ Operates safely at ambient temperatures of +120°F (+48°C)
- ▶ Meets FCC CLI regulations
- ▶ Includes external Class II UL approved power transformer

750 MHz Jr

- ▶ 32 dB gain incorporates 860 MHz hybrid in our standard 750 MHz chassis
- ▶ Flatness & return loss above 750 MHz are diminished from normal 750 MHz parameters
- ▶ Model performs better than low cost transistor 1 GHz amplifiers
- ▶ Higher gain of this model limits CTB performance for higher channel loading
- ▶ The low-gain models are recommended for high channel loading performance






QDE-Jr Specifications

SPECIFICATIONS		QDE-Jr Sub*		QDEJ860	
BANDWIDTH (MHz)		5-45	5-200	40*-860	
FREQUENCY RESPONSE		+/- 1 dB	+/- 1 dB	+/- 2 dB	
GAIN CONTROL RANGE		Pad	Pad	Pad	
SLOPE CONTROL RANGE		n/a	n/a	n/a	
RETURN LOSS		16 dB	16 dB	14 dB	
TEST POINTS (-30 dB, +/- 1 dB)		n/a	n/a	No	Yes
OUTPUT LEVELS (dBmV Flat)		48	48	38	40
INPUT/OUTPUT FILTERS (MHz)		LPF(50)	n/a	30,40**	30,40**
GAINS AVAILABLE (dB)		17,20	17,21	17,21	28,32
CHANNEL LOADING		4	26	128	49
DISTORTIONS	CROSS MOD. (-dB)	79	63	68	66
	COMP. TR. BT. (-dB)	86	70	62	67
	COMP. 2nd ORD. (-dB)	n/a	n/a	63	59
NOISE FIGURE		6 dB	5.5 dB	9 dB	9 dB
DC AMPERES @ 24 VDC		0.22	0.22	0.22	0.34
POWER DISSIPATION (Watts) ⁽¹⁾		12	12	12	16
OPERATING TEMPERATURE		0°C to +50°C (+32°F to +122°F)			
HUMIDITY		20%-55% (without condensation)			
DIMENSIONS		4.66"H x 5.0"W x 2.28"D (11.84H x 12.7W x 5.79D cm)			
WEIGHT		3.0 lbs (1.36 kg)			
NOTES: Test points are not available on 1-way amplifiers with gain below 22 dB. All 2-way models may be ordered with or without test points. All models with gain of 25 dB or more have test points included. Composite Triple Beat (CTB) and Cross Modulation specifications are given for 2-way models. Add 1 dB for 1-way amplifiers. (2-way amp CTB is -65 dB, same hybrid in 1-way amplifier has -66 dB CTB performance.) * Lower limit of forward bandwidth for 1-way models. 2-way bandwidth will be 50 MHz to model upper limit. ** The return bandwidth is 5-30 MHz. Special orders for 5-40 MHz require minimum quantity order. (1) Power dissipation at 120 VAC.					

QDE-Jr Distribution & Drop Amplifier:

Ordering Information

Example Part Number: QDEJ 750 - 32 2W /2	
<div style="display: flex; justify-content: space-around; width: 100%;"> 1 2 3 4 </div>	
1: Upper Frequency Limit:	45 = 5-45 MHz 200 = 200 MHz 550 = 550 MHz 750 = 750 MHz 860 = 860 MHz
2: Gain (See Specifications Table)	
3: Amplifier Configuration:	2W = 2-way Blank = 1-way
4: Test Point Options:	/2 = with Test Point /1 = without Test Point
Part Number	Description
Options & Spares	
QDERA-20	20 dB Return Amplifier
QEJ-xxx-xx	Forward EQ Value in MHz and dB Ratings
	
SXP-**	Plug-in Attenuator Pads, ** = 0-20 dB in 1 dB steps
	SXP Pads 
#951	120 to 26 VAC, 60 Hz AC Power Transformer, 50 VA Rating
	#951 Transformer 

MDU Solutions® is a registered trademark of ATX in the United States and/or other countries. Products or features contained herein may be covered by one or more U.S. or foreign patents. Other non-ATX product and company names mentioned in this data sheet are the property of their respective companies.



Specifications subject to change without notice.

